



## ITALMOSQUITO Series

**MAGICO** Line - Mosquito system



**PREMIUM**

I. 400 x P 240 x H 520 mm



**EVOLUTION**

I. 400 x P 240 x H 520 m



**KING**

I. 500 x P 250 x H 720 mm



HP pump equipped with Scudokal anti calcium scale component. Total protection on hydraulics circuits and nozzles.

EN - Mosquito misting system **Italmosquito** sprays water and pesticide mixsture at predetermined intervals to repel and kill mosquitos. Done properly, this system is supresingly effective.

### How it works?

Italmosquito misting system include medium pressure pump, pipes and spry nozzles mounted around the perimeter of a home in the lawn or landscaping or on parts of the house or fence. At predetermined times, Italmosquito releases product into the air to kill mosquitoes and prevent them from breeding. The mosquito misting system runs periodically, from a tank, in much the same way a sprinkler system does.

### Italmosquito main features

- Wall mounted box with pump, device control, tank for pesticide.
- Roll pipes
- Nozzles and fittings to create a line along the perimeter.

The programmable device control permits to organize the interval of work thanks to the calendar. Every day it is possible to switch on 17 time automatically the system for the minimum one minute. The automatic control inside the system alert with a led and acustic ring when the product/pesticidte is running out.

The whole system is easy to assemble.

**Italmosquito** the professional and automatic solution to repel and kill mosquitos.



**Medium pressure system - 20bar from 5 up to 80 nozzles**  
**230V - 50/Hz**

Italmosquito kits

- PREMIUM**- SINGLE PRODUCT- up to 80 linear meters
- EVOLUTION** - SINGLE PRODUCT - up to 160 linear meters
- KING** - DOUBLE PRODUCT - up to 280 linear meters

The kits don't include pesticide.

The Evolution and King model are also remotely manageable with a dedicated app (Ios/Android)

### FEATURES

- Rotative medium pressure pump
- Working pressure: 20 bar
- Automatic picking up products
- Cover in Sinkplat material
- Antivibrating rubber feet
- Stainless Stell glycerine filled pressure gauge
- Single phase motor with therml protection  
230V 1400 round/min -
- Switch ON/OFF + Timer
- Daily programmer and 17 daily start/stop
- No product controller.
- Low noise level: 25 dB(A)
- Manufactured in compliance with CE regulations
- Kit with pipes, nozzles, fittings